XH型鑽夾頭 XH TYPE KEYLESS DRILL CHUCK HEADS










■適用於銑床、鑽床及重型鑽加工。

- ■高精度超強鑽夾頭。
- ■剛性好,扭距大。
- Suitable for milling & drilling machine and heavy duty drilling use.
- High precision super drill chucks.
- Good rigidity allows high torque.

精度與扭矩表 Run-out Accuracy & Torque Inspection Table



單位/Unit:mm

1 1					
型號/TYPE	d	L	跳動/RUN-OUT	扭矩/TORQUE	
6XHSP	3	35	0.05	80	
07035	6	55	0.05		
8XHSP	3	35	0.05	160	
10XHSP	8	50			
	3	35	0.05	260	
	10	60			
13XHSP	5			400	
	10	55	0.05		
	13	75			
16XHSP	5			480	
	10	55	0.05		
	16	80			

48 🐔

型號/TYPE	夾持能力/CLAMPING	錐孔或直柄類型	D	А	В	重量WT(g)	QTY Pcs/Cu-Ft	淨/毛重NW/GW(Kgs)
6XH	0.5~6.5 [1/64"~1/4"]	J1	34.0	69	61	320	8/0.6	26/27
		B10	34.0	69	61	320	8/0.6	26/27
		B12	34.0	69	61	320	8/0.6	26/27
8XH	0.5~8.0 [1/64"~5/16"]	J1	34.0	69	61	340	40/0.6	14/15
		J2S	34.0	69	61	340	40/0.6	14/15
		B10	34.0	69	61	340	40/0.6	14/15
10XH	0.5~10.0 [1/64"~3/8"]	B12	43.0	92	81	700	40/0.6	28/29
		J2S	43.0	92	81	700	40/0.6	28/29
		J2	43.0	92	81	700	40/0.6	28/29
		J33	43.0	92	81	700	40/0.6	28/29
13XH	0.5~13.0 [1/64"~1/2"]	B12	51.5	103	92	1030	30/0.6	31/32
		B16	51.5	103	92	1030	30/0.6	31/32
		J2	51.5	103	92	1030	30/0.6	31/32
		J6	51.5	103	92	1035	30/0.6	31/32
		J33	51.5	103	92	1030	30/0.6	31/32
16XH	3.0~16.0 [1/8"~5/8"]	J6	58.0	108	95	1370	24/0.6	33/34
		B16	58.0	108	95	1370	24/0.6	33/34
		B18	58.0	108	95	1365	24/0.6	33/34
		J3	58.0	108	95	1340	24/0.6	33/34
		J33	58.0	108	95	1340	24/0.6	33/34