





OPTIONAL ACCESSORY:


• 7" 3-Jaw Chuck


Center Height of Tail Stock

Max. 165 mm Min. 38 mm

• The Universal Dividing Head can be used for Simple Dividing and also for producing worms, by changing gears and gear quadrant. A particular feature of the HOMGE design is the 55.5mm through bore and MT6 taper. Furthermore, the unit can also be tilted from 0 to 90 degrees.

- The Spindle, Worm and Gear are made of a high grade steel, hardened and ground for high accuracy and durability.
- The Tail Stock is designed with a dovetail construction for high rigidity and can be adjusted in each direction to achieve the correct alignment.
- The Worm and Gear provide a reduction ratio of 40:1 and the unit is supplied with a double sided Dividing Plate.
- Providing divisions on face A of 24, 25, 28, 30, 34, 37, 39, 41, 42 & 43 and on face B of 46, 47, 49, 51, 53, 54, 57, 58, 59, 62 & 66.
- The Change Gears supplied are 24, 28, 32, 38, 40, 44, 48, 56, 64, 72, 86 & 100 Teeth. Thus, a very wide and comprehensive range of indexing is achievable.
- · Each Universal Dividing Head is supplied complete with center, carrier, change gear quadrant, set of change gears, Tail Stock and Dividing Plate.





SPECIFICATIONS

SI ECITICATIONS																
	Model	Α		В		С		D		E		F		G		
	HCM-2	245	921/23	335	133/16	152	6	166	617/32	198	725/32	50	1 15/16	52	21/16	
	Model	ı	Н		h		J		К		L		Weight (kg)			
	HCM-2	143	55/8	285	117/32	194	7 5/8	465	185/16	265	107/16	132				