




Patent  
No.M417975  
No.M419629



IK-618L-RV(NC)





## SPECIFICATION

MODEL	Unit	IK-618L-RV(NC)	
<b>Spindle</b>			
Spindle Bore Diameter		NT50	
Diameter of Spindle Nose	mm	Φ128.6	
Spindle Motor	Hp	15(4P)	20(4P)
Step of Spindle Speed	stage	6	
Spindle Speed (50Hz)	rpm	110	326
		166	450
		220	675
Spindle Speed (60Hz)	rpm	132	392
		200	541
		265	810
<b>Working Range</b>			
Max Diameter of Cutter	mm	250	
Travel	mm	700(down)	
Rapid Travel AC Motor		0.75Kw/1Hp AC 3 Phase 4 Poles x 1/20	
Rapid Travel Speed	mm/min	358(50Hz)	
		428(60Hz)	
Reversal Slide		0.5mm/rev →  ← 0.01mm	

※We reserve the right to modify the design and specifications without notice in advance.



<b>STANDARD ACCESSORIES</b>		
Spindle Motor(15HP)		●
Rapid Travel AC Motor		●
Bearing Guide Screw		●
<b>OPTIONAL ACCESSORIES (APOLEGAMY)</b>		
Pneumatic Blade Locking Device		○
Pneumatic Leveler		○
IK-A90 Angular Head		○
IK-D90 Deep Head		○
IK-U90 Universal Head		○
IK-U45 Universal Head		○
Place of Origin	Taiwan	
Weight (Approximate)	kg	1300
Warranty	1 year (non artificial mistake)	

※We reserve the right to modify the design and specifications without notice in advance.

