



IK-V6000





SPECIFICATION

MODEL	Unit	IK-V6000	
<u>Spindle</u>			
Tapered Bore Diameter		BT50	
Spindle Speed	rpm	4500(Standard) 6000(Optional)	
Speed Change		High / Low	
<u>Deep</u>			
Distance from Spindle to Connector	mm	470	
<u>Gear Ratio</u>			
High Speed		1:1	
Low Speed		1:4	
Base Speed	rpm	375	
<u>Electric Use Standard</u>			
Spindle Motor	Kw/Hp	11/15	22/30
Spindle Motor Spindle		Φ48	Φ55
Gear Shift	rpm	1500	
<u>STANDARD ACCESSORIES</u>			
CNC Gear Milling Head - Vertical Spindle (4500RPM/BT50)		●	
Spindle Motor(Φ48)		●	-
Spindle Motor(Φ55)		-	●
Lock Knife Block		●	
Shift Cylinder		●	
Oil Pressure Pipe		●	
<u>OPTIONAL ACCESSORIES (APOLEGAMY)</u>			
CNC Gear Milling Head - Vertical Spindle (6000RPM/BT50)		○	
Place of Origin		Taiwan	
Weight (Approximate)	kg	532	
Warranty		1 year (non artificial mistake)	
<p>Note: This product does not contain a servo motor.</p> <p><u>Recommended specifications</u> §Spindle servo motor (11Kw / 15Hp or 22Kw/30Hp)</p> <p>※Please provide a servo motor sizes.</p>			

※We reserve the right to modify the design and specifications without notice in advance.