

手動攻牙鑽孔機

Manual Tapping & Drilling Machine



► HDT-32



► HDT-25



► HDT-340



規格 Specifications		型號 Model		
進刀方式 Stroke			HDT-340	HDT-25
			手動 Manual	手動 Manual
主軸型式 Spindle Type	主軸斜度 Inside Spindle	MT2	MT3	MT3
	鼻端斜度 For Chuck	JT6	JT6	JT6
工作能力 Working Ability (Steel S45C)	鑽孔能力 Drill Capacity	3-16	5-25	15-32
	攻牙能力 Tapping Capacity	3-13	5-20	15-32
主軸行程 Spindle Travel (mm)		100	140	140
馬達 Motor		1HP-4P	2HP-6P	2HP-6P
主軸轉速 (段數) Spindle Speed RPM (Steps)	50HZ	250-960 (9)	160-1342 (9)	55-175 (4)
	60HZ	300-1150 (9)	190-1610 (9)	65-210 (4)
重量 Weight (kg)		101	204	221

1. 實際工作能力與刀具銳利度、潤滑及冷卻有密切關係。

2. 特殊材質、尺寸須配合特製轉速。

1. The practical working abilities are very related to sharpness on drill bit, good lubrication and suitable cooling.

2. Customized spindle speed might be required for particular materials or drilling sizes.

- 實際工作能力與刀具銳利度、潤滑及冷卻有密切關係。
- 特殊材質、尺寸須配合特製轉速。
- The practical working abilities are very related to sharpness on drill bit, good lubrication and suitable cooling.
- Customized spindle speed might be required for particular materials or drilling sizes.

★ 外觀尺寸請參考 P.20 / 21
Appearance Dimensions Please View Page 20 / 21.