

HERG Service

FEATURES

- Power Supply System DC 5V / DC12V / DC 24V
- Line driver output available, besides open collector output.
- 25 PPR or 100 PPR Available
- Provide dimension Ø60 and Ø80 handle wheel to choose
- Multiple output type suit for many CNC controllers
- Dust and water proof short body and light weight design
- Protect inversion of polarity

Series	Model	type	DCPower	PULSE	Singal Mode	Diameter
HERG	T	A	5V	100PPR	A.B	60 Ø60mm
		B	5V	25PPR	A.B	80 Ø80mm
	F	C	12V	100PPR	A.B	
		D	12V	25PPR	A.B	
	T 60mm	E	5V Line Drive	100PPR	A.B.A/B/	
		F	5V Line Drive	25PPR	A.B.A/B/	
	F 80mm	G	24V	100PPR	A.B	
		H	24V	25PPR	A.B	
	I	I	8~26V Line Drive	100PPR	A.B.A/B/	
		J	8~26V Line Drive	25PPR	A.B.A/B/	

	PUSH-PULL	Voltage	Line Driver
SUPPLY VOLTAGE DC(V)	15±0.25~24v	5~15V	5+0.25 8~26V
CURRENT CONSUMPTION (mA)	≤ 70	≤ 60	≤120
MAX OUTPUT FREQU ENCY (kHz)	0~5	0~5	0~5
RISE TIME	≤ 1	≤ 1	≤ 1
FALL TIME	≤ 1	≤ 1	≤ 1
SINGLE LEVEL HIGH (VH)	≥ Vcc0.7	≥Vcc-1	≥2.5
SINGLE LEVEL LOW (VH)	≥ 1	≤ 0.5	≤ 0.5

