



KT-25 / 25L

Specification

Item	KT-25	KT-25L
Max turning diameter	360 mm	360 mm
Max turning length	500 mm	750 mm
Bar capacity	75 mm	75 mm
Chuck size	10"	10"
Spindle motor	15/18.5 kw	15/18.5 kw
Spindle speed	3500 rpm	3500 rpm
Spindle nose	A2-8	A2-8
X-axis travel	180+30 mm	180+30 mm
Z-axis travel	500 mm	750 mm
X-axis rapid feed rate	20 m/min	20 m/min
Z-axis rapid feed rate	20 m/min	20 m/min
Rail type	Box	Box
Tool capacity	10 T	10 T
Tailstock travel	425 mm	675 mm
Machine (LxWxH)	3508x1658x1854 mm	4070x1705x1844 mm
Machine weight	4500 kg	5200 kg



KT-30 / 30L

Specification

Item	KT-30	KT-30L
Max turning diameter	500 mm	500 mm
Max turning length	750 mm	1200 mm
Bar capacity	85 mm	85 mm
Chuck size	12"	12"
Spindle motor	15/18.5 kw	15/18.5 kw
Spindle speed	3000 rpm	3000 rpm
Spindle nose	A2-8	A2-8
X-axis travel	250+25 mm	250+25 mm
Z-axis travel	750 mm	1200 mm
X-axis rapid feed rate	20 m/min	20 m/min
Z-axis rapid feed rate	20 m/min	20 m/min
Rail type	Box	Box
Tool capacity	10 T	10 T
Tailstock travel	675 mm	1125 mm
Machine (LxWxH)	4307x1770x1942 mm	4786x1932x1941 mm
Machine weight	5700 kg	5900 kg