

V-40iT

五軸加工中心機

5-Axis Machining Center




- 入門款五軸機最佳選擇
- 適用於汽車、醫療、航太業
- 佔地面積小的五軸機
- 特殊角度及複雜曲面五軸加工
- 一體式工作台+多樣式盤面組合，可做彈性加工應用
- The best choice for an entry-level five-axis machine.
- Suitable for automotive, medical, and aerospace industries.
- Compact footprint five-axis machine.
- Capable of five-axis machining for special angles and complex surfaces.
- Integrated worktable with a variety of plate combinations for flexible machining applications.

機器特性FEATURES

V-40iT立式加工中心結合高速主軸（最高12000 RPM）和五軸同步加工技術，專為精密和複雜切削設計。這款機床在航空、模具及汽車行業的應用尤為出色，能夠處理多角度和高難度的任務。配有大型工作台和自動工具更換系統，提升了加工穩定性和生產效率。

The V-40iT Vertical Machining Center combines a high-speed spindle (up to 12,000 rpm) with five-axis synchronized machining technology, specifically designed for precision and complex cutting tasks. This machine excels in applications within the aerospace, mold-making, and automotive industries, capable of handling multi-angle and challenging operations. Equipped with a large worktable and an automatic tool change system, it enhances machining stability and production efficiency.



V-40IT

規格 SPECIFICATIONS

工作範圍

X軸行程
Y軸行程
Z軸行程

CAPACITY

X-axis travel 846mm
Y-axis travel 635mm
Z-axis travel 488mm

工作台

工作台面積
最大荷重
可傾斜角度

TABLE

Table size 400mm
Permissible mass 200/100kg
Tilting angle range +40°~-120°

主軸

主軸轉速
最大扭力

SPINDLE

Spindle speeds 12000rpm
Max. torque 70Nm

進給率

快速位移

FEEDRATE

Rapid traverse 36m/min

自動換刀系統

刀柄型式
刀具數

A.T.C.

Tool shank BT40
Tool storage capacity 24T

馬達

主軸馬達
伺服馬達

MOTORS

Spindle motor 15/18.5 kw
Feed motor 4kw

機台尺寸

電力
機台高度
外型尺寸(寬*深)

MACHINE SIZE

Power supply 35kva
Height 2930mm
Width x Depth 3315x2200mm



台灣麗偉電腦機械股份有限公司

LEADWELL CNC MACHINES MFG., CORP.

台中市后里區星科路8號

NO.8, XINGKE ROAD, HOULI DISTRICT,
TAICHUNG CITY 421007, TAIWAN

TEL: 886-4-25589008 FAX: 886-4-25589027