

CNC CYLINDRICAL GRINDER

OCA-H series

OCA-3235H



FEATURES

- The machine structure is strengthened with same design of heavy duty cylindrical grinder.
- The enlarge hydrostatic wheel spindle construction could equip max. 125 mm width grinding wheel for plunge grinding application.
- The large fully splash guard is designed for more interior space use.
- The taper fine adjustment tailstock is standard accessory and easy to adjust the taper if required.
- The variable frequency grinding wheel speed control could reach max. 60 M/s cutting speed.
- All the slides are hydrostatic designed for smooth move while grinding process.
- The optional accessories such as OD measuring system is possible to equip for clients use.
- The CNC conversational controller is ease of operation.

SPECIFICATIONS

CNC CYLINDRICAL GRINDER

OCA-3235H

| MODEL | OCA-3235H | |
|----------------------------|---------------------------------|----------------------------------|
| Capacity | Swing over table | Ø320 mm |
| | Distance between centers | 350 mm |
| | Max. external grinding diameter | Ø300 mm |
| Grinding Wheel | Max. load of centers | 150 kg |
| | O.D. x Width x I.D. | Ø610 x 80 (opt: 150) x Ø203.2 mm |
| Grinding Wheel head | Surface speed | 45 m/s |
| | Rapid speed | 10 m/min |
| Table | Min. setting unit | 0.001 mm |
| | Rapid speed | 10 m/min |
| Work spindle head | Min. setting unit | 0.001 mm |
| | Swivel angle | 0 ~ 10° |
| | Swivel angle | -30° ~ +90° |
| Tailstock | Center taper | MT. 4 |
| | Stroke | 25 mm |
| | Brand | FANUC |
| Motor | Wheel spindle | 11 kW (15HP x 4P) |
| | Workhead spindle | 0.8 kW AC servo |
| | Workhead spindle infeed motor | 2.5 kW (servo motor) |
| | Table infeed motor | 1.4 kW (servo motor) |
| | Hydraulic pump | 0.37 kW (6P) |
| | Wheel spindle lubrication pump | 0.37 kW (2P) |
| | Coolant pump | 0.18 kW (4P) |
| Tank Capacity | Wheel spindle lubricant tank | 18 L |
| | Hydraulic fluid tank | 60 L |
| Power | Total voltage | 27 KVA |
| | Pneumatic total pressure | 0.6 MPA |
| Machine Weight | Air consumption | 21 l/min (0.021 m³/min) |
| | Net weight | 5600 kg |

STANDARD ACCESSORIES

- CNC controller x 1
- Grinding wheel and wheel flange x 1
- Flange extractor x 1
- Linear scale (X axis) x 1
- Taper fine adjustment tailstock (±0.02 mm) x 1
- Cantilever crane for wheel change x 1
- Diamond tool holder (fixed type) x 1
- Hydraulic system x 1
- Coolant system x 1
- Work lamp x 1
- Tools and tool box x 1


OPTIONAL ACCESSORIES

- Fully enclosed splash guard
- Wheel balancing stand and arbor
- Auto. grinding wheel balancer
- Cam locked driving dogs (6 pcs/set)
- 2-point steady rest
- Touch probe gauge
- Auto. in-process gauge
- Gap control
- Magnetic coolant separator
- Magnetic and paper filter
- Oil mist collector

• The mentioned specifications & dimensions are subject to change without notice.

MACHINE DIMENSIONS

(unit: mm)



PALMARY

PALMARY MACHINERY CO., LTD.

No. 77, Gongye Rd., Dali Dist., Taichung City 41280, Taiwan.

Tel: +886-4-2492-9799 Fax: +886-4-2492-9499

E-mail: palmary@grinding.com.tw www.palmary.com



2006N2